



PRODUCT No.	THREAD TYPE	WIDTH ACROSS FLATS mm (in.)	WIDTH ACROSS CORNERS mm (in.)	THICKNESS mm (in.)	STANDARD	WEIGHT g (oz)
Stainless Steel Hex Nuts						
NS-03	#10-32 UNF	9.5 (3/8)	10.7 (7/16)	3.1 (1/8)	ANSI B18.6.3	1 (0.1)
NS-04	1/4" UNF	11.1 (7/16)	12.7 (1/2)	5.6 (7/32)	ANSI B18.6.3	3 (0.1)
NS-05	5/16" UNF	12.7 (1/2)	14.3 (9/16)	6.7 (9/32)	ANSI B18.2.2	5 (0.2)
NS-06	3/8" UNF	14.3 (9/16)	17.5 (11/16)	8.3 (10/32)	ANSI B18.2.2	6 (0.2)
NS-08	1/2" UNF	19.0 (3/4)	22.2 (7/8)	11.1 (7/16)	ANSI B18.2.2	17 (0.6)
NS-10	5/8" UNF	23.8 (15/16)	25.4 (1)	13.9 (9/16)	ANSI B18.2.2	34 (1.2)
NS-12	3/4" UNF	28.6 (1 1/8)	33.3 (1 5/16)	16.3 (5/8)	ANSI B18.2.2	54 (1.9)
NS-14	7/8" UNF	33.3 (1 5/16)	38.1 (1 1/2)	19.0 (3/4)	ANSI B18.2.2	85 (3.0)
NS-16	1" UNF	38.1 (1 1/2)	44.5 (1 3/4)	21.8 (7/8)	ANSI B18.2.2	128 (4.5)
NS-20	1 1/4" UNF	47.6 (1 7/8)	55.6 (2 3/16)	27.0 (1 1/16)	ANSI B18.2.2	260 (9.2)
NS-22	1 3/8" UNF	52.4 (2 1/16)	60.3 (2 3/8)	29.8 (1 5/32)	ANSI B18.2.2	450 (15.8)

PRODUCT No.	THREAD TYPE	FINISH	STANDARD	WEIGHT g (oz)
Brass Hex Nuts				
NB-03	#10-32 UNF	Nickel Plated	ANSI B18.2.2	1 (0.1)
NB-04	1/4" UNF	Nickel Plated	ANSI B18.2.2	3 (0.1)
NB-05	5/16" UNF	Nickel Plated	ANSI B18.2.2	5 (0.2)
NB-06	3/8" UNF	Nickel Plated	ANSI B18.2.2	8 (0.3)
NB-08	1/2" UNF	Chrome Plated	ANSI B18.2.2	19 (0.7)
NB-10	5/8" UNF	Chrome Plated	ANSI B18.2.2	36 (1.3)
NB-12	3/4" UNF	Chrome Plated	ANSI B18.2.2	60 (2.1)
NB-14	7/8" UNF	Chrome Plated	ANSI B18.2.2	98 (3.4)
NB-16	1" UNF	Chrome Plated	ANSI B18.2.2	145 (5.1)
NB-20	1 1/4" UNF	Chrome Plated	ANSI B18.2.2	266 (9.4)
NB-22	1 3/8" UNF	Chrome Plated	ANSI B18.2.2	180 (16.9)

PRODUCT No.	I.D. mm (in.)	O.D. mm (in.)	THICKNESS mm (guage)	WEIGHT g (oz)
Stainless Steel Flat Washers				
WS-03	4.8 (3/16")	11.1 (7/16")	0.9 20g	1 (0.1)
WS-04	6.4 (1/4")	14.3 (9/16")	1.2 18g	1 (0.1)
WS-05	8.0 (5/16")	16.0 (5/8")	1.2 18g	1 (0.1)
WS-06	9.5 (3/8")	19.0 (3/4")	1.2 18g	2 (0.1)
WS-08	12.7 (1/2")	25.4 (1")	2.0 14g	5 (0.2)
WS-10	16.0 (5/8")	38.0 (1 1/2")	2.0 14g	13 (0.5)
WS-12	19.0 (3/4")	38.0 (1 1/2")	2.0 14g	12 (0.4)
WS-14	22.2 (7/8")	41.3 (1 5/8")	3.0 10g	23 (0.8)
WS-16	25.4 (1")	47.6 (1 7/8")	2.0 14g	20 (0.7)
WS-20	31.8 (1 1/4")	70.0 (2 3/4")	3.0 10g	73 (2.6)
WS-22	36.0 (1 7/16")	66.0 (2 5/8")	5.0 -	80 (2.8)